<- Back **Product Description**

Title: LUMINAIRES, LUMINAIRES

FOSHAN LAND LIGHTING CO., LTD. - Foshan, Guangdong CHINA Company:

Product Trade Name(s): LD, Land Lighting, Brand Name.

Information:

Fixed LED Lighted Mirror, Model No. LED-5039.

Fixed LED Mirror, Model Nos. LED-5039. LED- or LEDB-; followed by 60 to 90; followed by 80 to 120; followed by -24, -36, -48 or -60.

Fixed Luminaire, Model Nos. WL-358, WL-359, WL-408, WL-409, WL-3509C, WL-3510-ICAT, WL-358-IC, WL-359-IC, WL-408-IC, WL-409-IC, WL-407-IC, WL-601-IC, LED-359-IC, WL-3509B-IC, WL-301-IC, WL-302-IC. PL107R-IC-7W- or PL109-GU10-IC-5W-; followed by two characters; followed by -; followed by two characters, EP-2610, EP-2620, EP-2630, WL-605-ICAT, WL-605.

Fixed Luminaire, Housing, Model Nos. LDWL-403-ICAT, LDWL-601-ICAT, LDWL-602-ICAT.

Fixed Luminaire, Trim, Model Nos. LDTM-4001, LDTM-6002. Model Nos. PL107R-IC-7W-XX-YY, PL109-GU10-IC-5W-XX-YY.

Fixture Lamp, Model Nos. LED-W001 or LED-W002; may be followed by A to Z; may be followed by W, B, N, AC, BL, BR, BZ, GD, RG, YE, OR or ORB.

Incandescent mirror luminaire, Model Nos. LEDHZ-6580.

LED Ceiling Light, Model Nos. TH-C12W, TH-C18W, TH-C24W.

LED Panel Light, Model Nos. TH-60120P, TH-6060P or TH-30120P; may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W, B, N, BR, BZ, BA or ORB.

LED Recessed Luminaire, Model Nos. LED-420 may be followed by -2700, -3000,-3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -8W, -9W, -10W, -11W or -12W.LED-420S may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -9W, -10W, -11W or -12W.LED-421 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -8W, -9W, -10W or -11W.LED-520 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -9W or -11W.LED-520S may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -12W or -13W.LED-620 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -12W, -13W, -14W or -15W.LED-620S may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -12W, -13W, -14W, -15W or -16W.LED-820 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -18W.LED-820S may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -18W or -19W.LED-320 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -6W or -7W.LED-421S may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -8W, -9W, -10W or -11W.LED-460 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB.LED-4018 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be

Contact Us

ETL listed products that are in doubt or for products that do not appear in the directory, please request a verification of certification. Americas+1-888-347-5478 (or +1-847-660-7407) Email etldirectory@intertek.com

> Intertek Home **Product Directories** DLP on mobile devices

Inspector Center

Get up-to-date information on everything from our Accreditations to our Certifications and Marks. Learn more...

News

Intertek Unveils New Design for Product Safety and Quality Certification Marks. Learn more...

or -13W.LED-1220 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -22W, -23W or -24W.LED-420T may be followed by W,B,N,BR,BZ or ORB; may be followed by -8W, -9W, -10W and -12W.LED-620T may be followed by W,B,N,BR,BZ or ORB; may be followed by -12W, -13W and -15W.LED-460-PAR20, LED-1220S, LED-6018, LED-X4, LED-X5 or LED-X6; may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB.LED-X3 or LED-X3T; may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -8W or -9W.LED-X4T, LED-X5T, LED-X6T, LED-4018T, LED-6018T, LED-520T, LED-520ST, LED-1220T, LED-1220ST or LED-320T; may be followed by W,B,N,BR,BZ or ORB.LED-420ST may be followed by W,B,N,BR,BZ or ORB; may be followed by -9W, -10W, -11W or -12W.LED-421T or LED-421ST; may be followed by W,B,N,BR,BZ or ORB; may be followed by -8W, -9W, -10W, -11W or -12W.LED-620ST may be followed by W,B,N,BR,BZ or ORB; may be followed by -12W, -13W, -14W or -15W.LED-820T or LED-820ST; may be followed by W,B,N,BR,BZ or ORB; may be followed by -18W or -19W.LED-380, LED-4701, LED-U3580, LED-4580, LED-423, LED-458 or LED-621 or LED-320S; may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB.LED-380T, LED-4701T, LED-U3580T, LED-4580T, LED-423T, LED-458T, LED-621T or LED-320ST; may be followed by W,B,N,BR,BZ or ORB.LED-423 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -12W.LED-423T may be followed by W,B,N,BR,BZ or ORB; may be followed by -12W. LED-320ST-7W.LED-320S may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -7W.LED-4702T may be followed by W,B,N,BR,BZ or ORB.LED-320F or LED-320SF; may be followed by W,B,N,BR,BZ or ORB.LED-420F may be followed by W,B,N,BR,BZ or ORB; may be followed by -8W, -9W, -10W and -12W.LED-420SF may be followed by W,B,N,BR,BZ or ORB; may be followed by -9W, -10W, -11W or -12W.LED-520F may be followed by W,B,N,BR,BZ or ORB.LED-520SF may be followed by W,B,N,BR,BZ or ORB.LED-620F may be followed by W,B,N,BR,BZ or ORB; may be followed by -12W, -13W and -15W.LED-620SF may be followed by W,B,N,BR,BZ or ORB; may be followed by -12W, -13W, -14W or -15W.LED-820F may be followed by W,B,N,BR,BZ or ORB; may be followed by -18W or -19W.LED-820SF may be followed by W,B,N,BR,BZ or ORB; may be followed by -18W or -19W.LED-1220F may be followed by W,B,N,BR,BZ or ORB.LED-1220SF may be followed by W,B,N,BR,BZ or ORB.LED-421SF may be followed by W,B,N,BR,BZ or ORB; may be followed by -8W, -9W, -10W, -11W or -12W.LED-621SF may be followed by W,B, N,BR,BZ or ORB; may be followed by -12W, -13W, -14W or -15W.LED-4018G may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -9W, -10W, -11W, -12W or -13W.LED-4018GT may be followed by W,B,N,BR,BZ or ORB.LED-4018F may be followed by W,B,N,BR,BZ or ORB.LED-4018GF may be followed by W,B,N,BR,BZ or ORB.LED-6018G may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB.LED-6018GT may be followed by W,B,N,BR,BZ or ORB.LED-6018F may be followed by W,B,N,BR,BZ or ORB.LED-6018GF may be followed by W,B,N,BR,BZ or ORB.LED- 458F may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB.LED-4581 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB.LED-4581T may be followed by W,B,N,BR,BZ or ORB.LED-4581F may be followed by W,B,N,BR,BZ or ORB.LED-4701G may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB.LED-4701GT may be followed by W,B,N,BR,BZ or ORB.LED-4701GF may be followed by W,B,N,BR,BZ or ORB.LED-4701F may be followed by W,B,N,BR,BZ or ORB.LED-4702 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B, N,BR,BZ or ORB.LED-4702G may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB.LED-4702GT may be followed by W,B,N,BR,BZ or ORB.LED-4702F may be followed by W,B,N,BR,BZ or ORB.LED-4702GF may be followed by W,B,N,BR,BZ or ORB.LED-621S may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -12W, -13W, -14W, -15W or -16W.LED-621ST may be followed by W,B,N,BR,BZ or ORB,may be fowllow by -12W,-13W, -14W,-15W. LED-422 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -8W, -9W, -10W, -11W or -12W.LED-422T may be followed by W,B,N,BR,BZ or ORB; may be followed

ORB; may be followed by -8W, -9W, -10W and -12W.LED-1020 may be followed by -2700,-3000,-3500,-4000,-5000,-6000, or -6500; may be followed by W,B,N,BR,BZ or ORB; may be followed by -22W,-23W.LED-1020T may be followed by W,B,N,BR,BZ or ORB.LED-1020F may be followed by W,B,N,BR,BZ or ORB.LED-1020S may be followed by -2700,-3000,-3500,-4000,-5000,-6000, or -6500; may be followed by W,B,N,BR,BZ or ORB.LED-1020ST may be followed by W,B,N,BR,BZ or ORB.LED-1020SF may be followed by W,B,N,BR,BZ or ORB.LED-380F may be followed by W,B,N,BR,BZ or ORB.LED-U3580F may be followed by W,B,N,BR,BZ or ORB.LED-423F may be followed by W,B,N,BR,BZ or ORB; may be followed by -12W.LED-621F may be followed by W,B,N,BR,BZ or ORB.LED-320SF may be followed by W,B,N,BR,BZ or ORB;may be followed by -7W.LED-X3F may be followed by W,B,N,BR,BZ or ORB; may be followed by -8W or -9W.LED-X4F may be followed by W,B,N,BR,BZ or ORB.LED-X5F may be followed by W,B,N,BR,BZ or ORB.LED-X6F may be followed by W,B,N,BR,BZ or ORB.LED-421F may be followed by W,B,N,BR,BZ or ORB; may be followed by -8W,-9W,-10W,-11W or -12W. Model Nos. PF-420 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W, B, N, BR, BZ or ORB; may be followed by -8W, -9W or -10W. LED-490T may be followed by W, B, N, BR, BZ or ORB. LED-490 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W, B, N, BR, BZ or ORB. PF-420T, PF-420F, LED-R12T or LED-R12F; may be followed by W, B, N, BR, BZ or ORB.LED-408 or LED-408T; may be followed by W,B,N,BR,BZ or ORB.PF-421 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W, B, N, BR, BZ,CH or ORB; may be followed by -8W, -9W or -10W.PF-320T, PF-320F, PF-4018GT, PF-4018GF, PF-6018GT, PF-6018GF, PF-820T, PF-820F, PF-1020T, PF-1020F, PF-1220T, PF-1220F, PF-1220ST or PF-1220SF; may be followed by W, B, N, BR, BZ,CH or ORB.PF-420T,PF-420F,PF-421T or PF-421F; may be followed by W, B, N, BR, BZ,CH or ORB; may be followed by -12W.PF-420ST, PF-420SF, PF-421ST or PF-421SF; may be followed by W, B, N, BR, BZ,CH or ORB; may be followed by -9W or -12W.PF-620T, PF-620F, PF-620ST, PF-620SF, PF-621T, PF-621F, PF-621ST or PF-621SF; may be followed by W, B, N, BR, BZ,CH or ORB; may be followed by -12W or -15W.

LED Trim Retrofit Recessed Downlight, Model Nos. LED-408, LED-606.

Low voltage luminaire, Model Nos. MN-2201LED. LED-SP26 followed by -2700, -3000, -4000, -5000 or -6000; followed by -0.17W or -1W. LED-2202 may be followed by S; followed by -2700, -3000, -4000, -5000 or -6000.Model Nos. MN-2201LED may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W, B, N, BR, BZ, CH or ORB.LED-SP26 may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by -0.17W or -1W.LED-2202 may be followed by S; may be followed by -2700, -3000, -3500, -4000, -5000, -6000 or -6500; may be followed by W, B, N, BR, BZ, CH or ORB.

Recess Lamp, Model Nos. WL-303-ICAT, WL-301-AT, WL-302, WL-509A-ICAT, WL-506A-ICAT, WL-509A-AT, WL-506A, WL-412, WL-405-IC, WL-407-IC, HR-359, HR-409, WL-407ICAT-LED, WL-601ICAT-LED, WL-405ICAT-LED, WL-602ICAT-LED, WL-403ICAT-LED, WL-506ICAT-LED, WL-509ICAT-LED, LED-413-ICAT, LED-513-ICAT, LED-613-ICAT.

Recessed Luminaries, Housing, Model Nos. LD-PLVA- followed by 403IC, 601IC, 602IC. Model No. LDHR-405. Model Nos. LDWL- followed by 403-ICAT, 601-ICAT, 602-ICAT.

Recessed Luminaries, Trim, Model No. TM-4001 used for Model No. LD-PLVA-403IC only. Model No. TM-602IC used for Model Nos. 601IC, 602IC only. Model No. LDTH-4001. Model No. LDTM-4001 used for Model No. LDWL-403-ICAT only. Model No. LDTM-6002 use for Model Nos. LDWL-601-ICAT, LDWL-602-ICAT only.

Evaluated to the following:

A representative sample of the listed devices have been tested, investigated and found to comply with the requirements of the Standard(s) for Luminaires (CAN/CSA-C22.2 No. 250.0) and are identified with the cETL Listed Mark.; A representative sample of the listed devices have been tested, investigated and found to comply with the requirements of the Standard(s) for Luminaires (CAN/CSA-C22.2 No. 250.0) and are identified with the cETL Listed Mark.

© 2010 Intertek All Rights Reserved. All other product or service names are the property of their respective owners.